



# **TITAN AG**Analogue PIR Detector

## EN 50131 GRADE 2 Class II

#### Description

TITAN AG is an analogue PIR detector suitable for use in residential, commercial and office buildings. TITAN AG has high white light immunity and pet immunity for animals up to 12 kg. The detector is also equipped with adaptive temperature compensation. TITAN series detectors have a 5-year warranty.

As an option the detector can come with bracket for wall or ceiling mounting.

#### Technical and Environmental Specifications

Coverage Range..... from 1.5 to 15m

Standard Mounting Height. . . . . 1.5m - 3.6m (recommended 2.1m)

White Light Immunity . . . . . . 6500 lux Electrostatic Immunity . . . . . 8 kV

RF Immunity . . . . . . . . . . . . . . . 10V/m@80MHz-2.7GHz

Pet Immunity . . . . . . . . . . small animals up to 12 kg

Walk Detection Speed . . . . . . 0.2m/s - 3.5m/s Operating Temperature . . . . . from -20 up to 50°C Power Supply . . . . . . . . . 9 VDC to 18 VDC

Current Consumption . . . . . < 12mA Weight . . . . .  $\sim$  74g

Dimensions . . . . . . . . . . . . 62 x 97 x 50mm

### Packing Information

• Master box - 100 units TITAN AG, dimensions 542 x 334 x 286 mm

#### Compatible Product Range

- Bracket for wall mounting
- ECLIPSE series alarm control panels





Tel.:+359 2 9694 800

Fax: +359 2 9625 213